

Product Specifications

FlashLink PDF VU In-Transit Logger

Measurement Range	-40°F to 122°F (-40°C to 50°C)
Temperature Resolution	0.1 °F/°C
Accuracy	±1.0°F from -4°F to 113°F, (±0.5°C from -20°C to 45°C); ±2.0°F above 113°F, (±1.0°C above 45°C); ±2.0°F below -4°F, (±1.0°C below -20°C);
Data Capacity	3,823 data points
Data Download Time	30 seconds typical for 3,823 points
Factory Programmable Alarm Levels	High/low limits over entire temperature range
Battery	Coin Cell Lithium battery
Battery Shelf Life	18 months
Dimensions	1.93" x 3.62" x 0.67" (49mm x 92mm x 17mm)
Casing	ABS plastic
Weight	1.6 oz. (45.36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
IP Rating	IP54
Display	LCD, Red LED Alarm
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
PDF Standards	RTCA/DO-160, Complies with ISO19005-1, PDF/A, 21 CFR Part 11
System Requirements	Windows PC with current operating system, Adobe Reader
Download Requirements	Direct USB connection
Certification	CE Mark, Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant



Models	40443
Logging Interval	10 minutes
Duration	15-Day
Temperature Scale	°F
Start Delay	30 minutes

- Single-use temperature logger
- Large, easy to read LCD display
- No software required to download data
- Built-in USB connector, no special reading devices needed
- Automatically creates secure PDF report and CSV file
- Trip history statistics available on LCD
- Patented Shadow Log® feature guarantees data even if the shipper fails to start the logger
- High/low alarm indicators
- Service available to custom configure logging parameters, alarms, delayed start

Patent No. 6,088, 514

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 40443 20L1

