


# Flash Check®

## Digital Pocket Probe Thermometer



**Model 11025**

The next generation digital pocket probe thermometer is engineered to set the industry standard for accuracy and durability. It is technically designed and constructed under exacting standards to meet and exceed the specifications required for commercial and industrial uses.

- Reduced tip probe thermometer provides 300% faster response time than conventional models
- Can be field calibrated
- Sealed unibody construction
- Water & grease resistant

PATENT NO. 5,709,476



Temperature Range	-40°F to 302°F (-40°C to 150°C)
Accuracy	±1°F (4°F to + 194°F ) ±0.5°C (-16°C to + 90°C); otherwise ±1.8°F (±1°C)
Resolution	0.1°F (0.1°C)
Display Update	Every 2 Second
Water Resistant Rating	IP56
Probe	Stainless steel probe, 3.5 in. (90mm) long Reduced probe tip .1 in. (2.3mm) diameter
Body/ Dimensions	Polycarbonate & ABS/ 6.75 in. (171.45mm) long
Calibration	Field calibratable. NIST traceable calibration certifiable. Manufacturers certificate of compliance available from DeltaTRAK
Battery	1.5V Button

**1-800-962-6776 • www.deltatrak.com**



P.O. Box 398 Pleasanton CA 94566 (925) 249-2250 Fax (925) 249-2251