

Temperature and Humidity Chart Recorder



Model 14001

24hr. record time (°F)
Replc. Chart 14101

Model 14002

8 day record time (°F)
Replc. Chart 14102

Model 14003

32 day record time (°F)
Replc. Chart 14103

Model 14004

24hr. record time (°C)
Replc. Chart 14104

Model 14005

8 day record time (°C)
Replc. Chart 14105

Model 14006

32 day record time (°C)
Replc. Chart 14106

- High-impact ABS casing
- Compact, wall mountable
- Replaceable charts
- Solid-state quartz clock motor
- Simultaneously records temperature and humidity

Temperature Range	14°F to 104°F (-10°C to 40°C)	
Accuracy: Temperature	±2°F (±1.0°C)	
Accuracy: Relative Humidity	+/-5% RH between 30% & 90% RH (Min.scale on chart:2%)	
Humidity Range	0 to 100% RH	
Sensor	Bi-metal coil: Temperature	Nylon Film: Humidity
Chart	6.6-in. (165 mm) diameter paper	
Drive	Quartz clock stepper	
Pen	Disposable fiber-tip	
Battery	AA alkaline (1 year shelf life)	
Weight	23 oz. (650 grams)	

Rev 5/9/08



DeltaTRAK

1-800-962-6776 • www.deltatrak.com

P.O. Box 398 • Pleasanton CA 94566 • (925) 249-2250 • Fax (925) 249-2251