

FLASHLINK[®] CT

Data Logger

Model CT

Model CTX

8 models available

Recording Period	Models with sleeve (CT)	Models without sleeve (CTX)	Logging Intervals
5-day	20720	20730	1 min. 54 sec.
15-day	20721	20731	5 min. 40 sec.
45-day	20722	20032	16 min. 58 sec.
75-day	20723	20733	28 min.16 sec.



- Compact, in-transit data logger
- Print data using CT Graphics Printer or download data to a PC using CT-USB adapter
- Patented *Shadow Log* feature guarantees data even when the unit is not activated

DeltaTRAK's FlashLink CT Logger is the ideal device for documenting storage and transport conditions of temperature sensitive products.

Internal Temp. Sensor & Operating Range	-40°F to 150°F (-40°C to 66°C)
Temperature Accuracy	±1.0°F (0.5°C) From 32°F to 150°F (0°C to 66°C) ±2.0°F (1°C) over entire range
Temperature Resolution	0.1°F/C
Data Capacity	3,822 data points
Data Download Time	5 second
Factory Programable Alarm Levels	High & Low levels over entire range
LED Indicators	Flashing red for alarm, green for active
Battery Type	lithium coin, 3v
Dimensions/Enclosure	3.44" L x 2.07" W x 0.57" H 87.38mm L x 52.72mm W x 14.65mm H ABS plastic case with protective utility case
Weight	CT: 1 oz. (28g) / CTX: 0.7 oz. (19 g.)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, Calibration Traceable to N.I.S.T. RoHS compliant
Min. System Requirements	IBM compatible 486 with 4MB RAM, WIN3.1, '95, '98, 2000, XP, or NT
Software Requirements	In-Transit FlashLink CT Software package #20176, including CT-USB adapter

PATENT NO.'s 6,088,514 & 6,142,298

08/26/08 Rev. 1.1



DeltaTRAK

1-800-962-6776

P.O. Box 398 Pleasanton CA 94566

www.deltatrak.com

(925) 249-2250 Fax (925) 249-2251