

# Product Specifications

## Industrial Control Computer

### Processor

<b>CPU</b>	Intel Core i7 5500U, 2C4T
<b>Frequency</b>	Base: 2.4GHz, Turbo: 3.0GHz
<b>BIOS</b>	American

### Memory

<b>Type</b>	1 single channel SODIMM slot, DDR3L 1066/1333/1600MHz
<b>Max Capacity</b>	8GB
<b>Socket</b>	1*204-pin SO-DIMM

### Display

<b>Integrated Graphics</b>	Intel HD Graphics 5500
<b>VGA</b>	Max. resolution 1920×1080@60Hz
<b>HDMI</b>	Max. resolution 3280×2000@60Hz
<b>Dual-Display</b>	VGA+HDMI, synchronous/asynchronous dual-display

### Audio

<b>Main System</b>	Audio control chip: Realtek ALC662, dual track, stereophonic, line out
--------------------	--

### Power Supply

<b>Power Type</b>	DC-IN5.5*2.5
<b>Input Voltage</b>	12V

### Power Consumption

<b>Min. Input</b>	3A
<b>Power Adapter</b>	DC 12V 3A/36W (AC TO DC, 100~240V)



### Model 15062

- Required hardware for running the FSTIS thermal imaging software application
- FSTIS thermal imaging software application comes pre-installed on the industrial control computer
- Features a fast Intel i7 processor and 8GB of memory to optimally run the software application
- Compatible with standard keyboard and mouse via USB port connection

SS 15062 20H2

