Product Specifications

Digital Display Environmental Temperature Recorder

Low Temp Range	-20°F to 100°F (-28°C to 38°C)		
High Temp Range	30°F to 150°F (0°C to 65°C)		
Accuracy	Chart and Scale: ±1.8°F (±1.0°C) LCD: ±1.8°F (-20°C to 165°C), ±1.0°C (-7°C to 74°C)		
LCD Display/Chart Window	1.5" x 0.5" (3.8cm x 1.3cm)/2" x 2.8" (5cm x 7.1cm)		
Sensor	Bi-metal coil/thermistor		
Chart	Pressure-sensitive 36-inch strip		
Drive	Solid-state quartz motor		
Certification	CE mark, RoHS compliant		
Battery	AAA alkaline (3-year shelf life; 1 to 2 years operating life)		
Weight	1.1 lb (500 grams)		
Dimensions	4in. x 7in.x 2.25in. (10.2cm x 17.8cm x 5.72cm)		
Casing Materials	High impact ABS		



Models	3-Day	10-Day	62-Day
High Range °C	18020	18024	18030
High Range °F	18021	18025	18031

	3-Day	10-Day	31-Day
Low Range °C	18022	18026	18028
Low Range °F	18023	18027	18029

- Highly visible LCD display and large window for viewing current and recently chart recorded temperature data
- Reusable, light weight, compact and battery operated, can be wall-mounted, or hung from a loop
- Wall-mounting bracket, screws and QC chart provided
- 12 models in °F and °C scales and two temperature ranges for 3-Day, 10-Day, 31-Day and 62-Day time intervals





P.O. Box 398 Pleasanton, CA 94566 USA | p (925) 249-2250 | (800) 962-6776 | f (925) 249-2251 | www.deltatrak.com

SS0033 13K1