

# Product Specifications

## FlashLink Electronic Data Logger

<b>Internal Temp Sensor Range</b>	-40°F to 150°F (-40°C to 66°C)
<b>Temperature Accuracy</b>	±1°F (0.5°C) at 32°F to 150°F (0°C to 66°C) ±2°F (1°C) over entire range
<b>Humidity Accuracy</b>	±5% at 50% RH at 25°C
<b>Operating Humidity Range</b>	1% to 99% RH
<b>Temperature Resolution</b>	0.1°F/C
<b>Logged Data Capacity</b>	10,339 data points
<b>Data Download Time</b>	5 second typical for 3,800 data points
<b>Programmable Alarm Levels</b>	High and Low Levels over entire range
<b>Startup Alarm Delay</b>	Skip 1 to 16 points
<b>Operating Alarm Delay</b>	0 to 79 minute delay filter
<b>Logging Time Interval Range</b>	3 seconds to 24 hours
<b>Programmable Delayed Start</b>	0 seconds to 256 days
<b>LED Indicators</b>	12-second flashing red for alarm; green for active
<b>Battery Type/ Life</b>	CR2450 3v lithium/ 1 year
<b>Dimensions/ Enclosure</b>	ABS plastic case, 3.25 x 2.25 x .75 in. (8.3 x 5.7 x 1.9 cm.)
<b>Water Resistance</b>	IP56
<b>Shock Resistance</b>	Withstands 3-foot drop to hard surface
<b>Certification</b>	CE Mark by T.U.V.; Calibration Traceable to N.I.S.T.
<b>Min. System Requirements</b>	IBM compatible 486 with 4MB RAM, Windows XP or Vista
<b>Software Requirements</b>	FlashLink Program Manager Software #20223



### Model 20207

- One internal temperature sensor and one internal humidity sensor
- Very easy to use and highly accurate
- Output charts, graphs, spreadsheets or email your results anywhere in the world

Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9000 registered quality management system

SS0054 13K1

