

Product Specifications

FlashTrak™ In-Transit Logger

| | |
|------------------------------|--|
| Measurement Range | -22°F to 140°F (-30°C to 40°C) |
| Radio Frequency Range | up to 250M (820 ft) line of sight |
| RF Bands | 915 MHz 868 MHz ISM band (available by special order) |
| Sample Interval | Factory programmable. Default setting: 5 min. |
| Resolution | 0.2°F (0.1°C) |
| Accuracy | ±0.3°C for 12 months after calibration |
| Data Capacity | 2,730 data points |
| Power Source | MnO ₂ Battery |
| Battery Life | up to 2.5 yrs 5 yr shelf life |
| Weight | 2.65 oz |
| Dimensions | 59mm x 106mm x 17mm (2.32 in x 4.17 in x 0.66 in) |
| LED Indicator | Green – Sending data |
| Waterproof Rating | IP67 |
| Certification | FCC, CE, RoHS, WEEE, NIST |



Model 22079

- Wireless data logger for FlashTrak Telematics System
- Non-invasive internal product monitoring with Product Emulation
- Data visible 24/7 on ColdTrak Data Central cloud service
- Alert notifications with four set points: high and extreme high, low and extreme low
- Security wall mount bracket

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 22079 17H2

