Product Specifications

FlashLink® Real-Time In-Transit Logger

Temperature Range	-4˚F to 131˚F (-20˚C to 55˚C)
Temperature Accuracy	±0.6°F (0.3°C) over full temperature measurement range
Temperature Resolution	0.015 °F/°C
Humidity Measurement Range	0% to 100% RH
Humidity Accuracy	±2% from 0% RH to 90% RH ±3% from 90% RH to 100% RH stated within temperature exposure range of 41°F to 131°F (5°C to 55°C), non-condensing
Humidity resolution	0.01% RH
Light Sensor	Dual Stage Sensor
Shock Sensor	3-axis G sensor
GSM Network	Quad band GSM 850/900/1800/1900 MHz
SIM	Global data roaming
Power Source	Lithium-ion Battery
Battery Life	12 month shelf life (non-active)
Weight	7.76 oz (220 grams)
Logger Dimensions	4.92 in Dia. x 1.18 in (125 mm Dia. x 30 mm)
Waterproof Rating	IP54
Certification	FCC, CE Mark, Temperature & Humidity Sensor NIST traceable

Model	Duration	Logging Interval & Data Upload
22301	100-Day	60 Min

- Monitors location, temperature, humidity, light, shock
- Data transmitted via GSM cellular networks
- No need to open vehicle doors to access information
- 24/7 cloud service to view and analyze data remotely
- Make immediate cold chain management decisions
- Reroute trucks when necessary
- Customize settings for high/low alarm limits
- Data stored in the cloud for traceability, audits, HACCP, and FSMA compliance

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 22301_19D1

DeltaTrak®

P.O. Box 398 Pleasanton, CA 94566 USA | p (925) 249-2250 | (800) 962-6776 | f (925) 249-2251 | www.deltatrak.com