

## FlashLink. RTL Prime In-Transit Logger

<b>Temperature Range</b>	-4°F to 158°F (-20°C to 70°C)
<b>Temperature Accuracy</b>	±0.9°F from 14°F to 113°F (±0.5°C from -10°C to 45°C) ±2°F if <14°F and >113°F (± 1°C if < -10°C and > 45°C)
<b>Temperature Resolution</b>	0.1 °F/°C
<b>Data Capacity</b>	28,800 data points
<b>Logging Interval</b>	Factory programmed
<b>GSM Network</b>	2G Quad band GSM 850/900/1800/1900 MHz, GPRS data
<b>SIM</b>	Internal Embedded (Global Data Roaming)
<b>Power Source</b>	Lithium-ion Battery
<b>Battery Shelf Life</b>	1 year
<b>Weight</b>	1.83 oz (52 grams)
<b>Logger Dimensions</b>	2.13 in x 3.89 in x 0.37 in 54 mm x 85 mm x 9.4 mm
<b>Certification</b>	FCC, CE Mark, RoHS, WEEE, Temperature Sensor NIST traceable
<b>System Requirements</b>	PC with internet access to view data on the cloud
<b>Download Requirements</b>	Direct USB connection, Micro USB to USB cable required



Model	Trip Duration	Logging Interval
22362	15-Day	10 Min

- Monitors location and temperature
- Data transmitted via GSM cellular networks
- No need to open vehicle doors to access information
- 24/7 cloud service to view and analyze data remotely
- Make immediate cold chain management decisions
- Customize settings for high/low alarm limits
- Data stored in the cloud for traceability, audits, HACCP, and FSMA compliance
- Extended battery life

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 22362\_20A2

