

Product Specifications

FlashLink® NOW AIR 4G/5G Real-Time In-Transit Logger

| | |
|--------------------------------|--|
| Temperature Range | -30°C to 70°C (-22°F to 158°F) |
| Temperature Accuracy | ±0.5°C from -10°C to 45°C (±0.9°F from 14°F to 113°F), ±1.0°C (±2.0°F) Other |
| Temperature Resolution | 0.1°C/°F |
| Temperature Sensor Type | Internal Digital Temperature Sensor (NIST traceable) |
| Humidity Range | 5% to 95% RH |
| Humidity Accuracy | ±3% from 20% to 80%RH ±5% for other |
| Light Sensor Range | 0 to 52000 lux |
| Light Detecton Accuracy | 0.01 lux |
| Shock Sensor | 0-8g height: 5-10cm |
| Usage Type | Single-use |
| Data Capacity | Max 28800 readings |
| Logging Interval | 5 Min. |
| Data Upload Interval | 15 Min. |
| Trip Duration | 15-Day (based on logging and uploading intervals) |
| Cellular | Global LTE Cat-1 4G/5G network, with 2G Fallback |
| SIM | Internal Embedded (Global Data Roaming) |
| Power Source | Non-Lithium, NiMH, meets UN38.3 |
| Battery Shelf Life | 6 months |
| Logger Dimensions | 4.05in x 2.41in x 1.18in (103mm x 61.3mm x 30mm) |
| Weight | 4.9 oz (140 g) |
| Waterproof Rating | IP64 |
| Certification | FCC, CE, UN38.3, RTCA/DO-160G, RoHS, NIST traceable temperature accuracy, WEEE |
| PDF Report Backup | Micro USB to USB cable to download full trip PDF report |

Available starting January 2023

DeltaTrak manufactures and operates under an ISO 9001:2015
registered quality management system



Model 22493-01

- Non-Lithium Battery
- Next generation of global cellular communications real-time loggers with LCD using 4G/5G LTE/2G
- Monitors location, temperature, humidity, light, shock and air pressure
- Temperature shown in °F
- Proactively manage shipment location and conditions to reduce the risk of product loss due temperature excursions
- FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions
- USB option to download PDF trip data should GSM network not be available.
- Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation
- Maritime tracking service options ensure access to different modes of integrated supply chain data.

SS 22493-01 23A2

