

Product Specifications

FlashLink Mini In-Transit Logger

Operating Range	-40°F to 150°F (-40°C to 66°C)
Temperature Accuracy	±1.0°F (0.5°C) From 32°F to 150°F (0°C to 66°C) ±2.0°F (1.0°C) over entire range
Temperature Resolution	0.1°F/°C
Data Capacity	3,823 data points
Data Download Time	5 seconds
Factory Programmable Alarm Levels	High & Low levels over entire range
LED Indicators	Flashing red for alarm, green for active
Battery Type	Lithium Coin cell
Dimensions/Enclosure	2.68" L x 1.27" W x 0.45" H (68.07mm L x 32.25mm W x 11.43mm H) ABS plastic case
Weight	0.64 oz. (18.14g)
Certification	CE Mark, Calibration Traceable to N.I.S.T., RoHS Compliant, BSS 7061 Compliant
System Requirements	Windows PC with current operating system, Adobe Reader, FlashPDF software
Download Requirements	8-Pin to USB Adapter



Models	5-Day	15-Day	45-Day	75-Day
Logging Interval	1 min. 54 Sec	5 min. 40 Sec	16 min. 58 Sec	28 min. 16 Sec
°F/°C	30013	30014	30015	30016

- Ideal for documenting storage and transport conditions of temperature sensitive products
- Compact, single-use, in-transit data logger
- Print data using CT Graphics Printer or download to a PC using 8-pin to USB adapter
- Patented Shadow Log™ feature guarantees data if the shipper fails to start the logger
- Includes Shipping Bag

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0120_16C3

