

Product Specifications

FlashLink Mini Seafood In-Transit Logger

Recording Period	15 Days
Logging Interval	5 min, 40 sec
Measurement Range	-40°F to 122°F (-40°C to 50°C)
Temperature Resolution	0.1°F/°C
Temperature Accuracy	±1.0°F (0.5°C) From 32°F to 122°F (0°C to 50°C) ±2.0°F (1.0°C) over entire range
Data Capacity	3,823 data points
Data Download Time	5 seconds typical for 3823 points
Alarm Settings	38°F high alarm/32°F low alarm (3°C high alarm/0°C low alarm)
LED Indicators	Flashing red for alarm, green for active
Battery	Coin Cell Lithium Battery
Logger Dimensions	2.68" L x 1.27" W x 0.45" H (68.07mm L x 32.25mm W x 11.43mm H)
Casing	ABS plastic
Logger Weight	0.64 oz. (18.14g)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, Calibration Traceable to N.I.S.T., RoHS Compliant,
IP Rating	IP56
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system, Adobe Reader, FlashPDF software
Download Requirements	8-Pin to USB Adapter



Model 30028

- Compact, single-use, in-transit data logger
- Document temperature during transport to meet FSMA and FDA requirements
- Approved by most receivers
- Consolidate logger inventory with one brand for all shipments
- High/Low alarms programmed for seafood products
- Mounted on high-visibility locator card
- Water-resistant plastic shipping pouch
- Patented Shadow Log™ feature guarantees data if the shipper fails to start the logger
- Download data to PC as secure PDF report or print chart using CT Graphics Printer

Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0172_16C2

