


# Product Specifications

## FlashLink Certified Vaccine USB PDF Data Logger

<b>Sensor Measurement Range</b>	-58°F to 104°F (-50°C to 40°C)
<b>Operating Range</b>	-58°F to 77°F (-50°C to 25°C)
<b>Temperature Resolution</b>	0.1°F/°C
<b>Accuracy within Normal Operating Range</b>	±1.0°F from -58°F to 77°F (±0.5°C from -50°C to 25°C)
<b>Data Capacity</b>	32,496 data points
<b>Data Download Time</b>	5 seconds typical for 3823 points
<b>Multiple Alarm Levels</b>	High & low levels and extreme high and low levels displayed on LCD, with audible buzzer
<b>Battery</b>	Two AAA lithium batteries, LCD % remaining power indicator
<b>Dimensions/Body</b>	1.575 in x 3.66 in x 0.94 in (40 mm x 93 mm x 24 mm)
<b>Casing</b>	ABS plastic
<b>External Sensor</b>	Thermistor in 5ml PETG* Sterile Bottle - 21CFR compliance information available, 3 meter cable with quick disconnect
<b>Glycol Buffer</b>	Propylene glycol (GRAS** classified)
<b>Weight</b>	3.2 oz. (90.7 grams)
<b>Certification</b>	2 year ISO 17025 calibration certificate, CE Mark, Manufacturer's Certificate of Compliance, RoHS compliant. Reference standards traceable to International System of Units (SI) through NIST.
<b>Display</b>	LCD, Red LED Alarm
<b>Waterproof Rating</b>	IP64 (with silicone cap)
<b>Storage conditions</b>	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
<b>Shelf Life</b>	2 years (battery life)
<b>System Requirements</b>	Windows PC with current operating system, Adobe Reader
<b>Programming</b>	Supplied preconfigured for either refrigerator or freezer. User programmable using included FlashPDF Program Manager software.
<b>Download Requirements</b>	Direct USB connection to PC (No special software required to download logger.)
*Polyethylene terephthalate copolymer, **Generally Recognized As Safe	



### Model 40527

Includes ISO 17025 Calibration Certificate from A2LA accredited lab, valid for 2 years. Reference standards traceable to International System of Units (SI) through NIST.

- WHO Prequalified E006 Temperature Monitoring Device
- Compatible with CDC guidelines
- 21 CFR Part 11 compliant
- Single channel, external sensor in glycol bottle
- Automatically generates encrypted PDF, CSV and Daily Log reports
- Automatically generates PDF report and CSV file
- Glycol buffered sensor emulates products and prevents false alarms
- Ideal for monitoring vaccines and liquid medicines during storage
- Audible and/or visual alarms
- Low battery indicator on LCD
- Quick disconnect cable to download logger
- User programmable: manual or auto start, logging intervals, hi/low alarms
- Scroll through recorded data on LCD

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 40527 18C1

