

Product Specifications

FlashLink In-Transit BLE Temperature & Humidity Logger

Measurement Range	-30°C to 70°C (-22°F to 158°F)
Temperature Accuracy	-30°C to -25°C: ±1.0°C (-22°F to -13°F: ±1.0°F) -25°C to +70°C: ±0.5°C (-13°F to 158°F: ±0.5°F)
Humidity Range	0% to 100% RH
Humidity Accuracy	±5% RH at 25°C
Data Capacity	28800 data points (14400 for temp 14400 for humidity)
Logging Interval	10 minutes
Recording cycle	Up to 90 days
Start mode	Manual
Stop mode	Manual/Data limit/USB connection
Transmission Range:	5 seconds interval/65 ft (20m) at sight
Shelf Life	1 year
Battery	3.0v lithium battery
Dimensions/Body	1.575 in x 3.189 in x 0.492 in (40 mm x 81 mm x 12.5 mm)
Casing	ABS plastic
IP Rating	IP64 (with silicon cap on)
Weight	1.9 oz. (54 grams)
LED	Blue and Red
Certification	NIST traceable, CE Mark, FCC RoHS compliant
System Requirements	iOS or Android 6.0.1, and Bluetooth 4.0 Requires internet access to save data to the cloud
Bluetooth Connection	Android™/iOS® App
On-Line Tracing	Customized Web portal



Model 40910

- Monitors temperature, humidity and location
- Tracks route and conditions inside vehicles during delivery
- Tracks conditions in storage, processing and packing facilities
- Access data on mobile device up to ~65 feet /20 meters away
- Secure data is viewed on demand
- No need to open doors and locate logger for downloading
- Wirelessly transmits data to smart devices with app
- Customize settings: ID/name, logging interval, high/low alarm limits
- Access PDF reports from direct USB connection or through the APP
- Data stored in a cloud-based application

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system

SS 40910 20H1

